

The SQG3 AV is a combined audible and visual base unit. The large flast surface allows the mounting of most popular European detectors, while the high efficiency and low operating current permit compatibility with many systems.

## **Features**

- Fixing platform for most popular detectors
- Low current consumption
- Tamper proof cap for standalone use (supplied separately)
- First fix base for easier installation
- LED triggered option available


# **Benefits**


- Save on installation costs
- Notification and detection in one unit

### **Technical Specification**

| Voltage        | 18 - 28Vdc                |  |
|----------------|---------------------------|--|
| Current        | 4/5mA                     |  |
|                | 9mA (AV version)          |  |
| Sound Output   | 90dB(A)                   |  |
| Tones          | 8                         |  |
| Volume Control | 10dB                      |  |
| Light Output   | >1Cd                      |  |
| Flash Rate     | 1Hz                       |  |
| Monitoring     | Reverse polarity          |  |
| Temperature    | - 10°C to + 55°C          |  |
| Protection     | IP21C                     |  |
| Construction   | ABS                       |  |
|                | ABS, PC lens (AV version) |  |
| Weight         | 0.16Kg                    |  |
| Colours        | White                     |  |
| Flash Colour   | Red                       |  |
|                |                           |  |

# Dimensions





#### **Catalogue Numbers**

| Reference | Cat No           | Description         |
|-----------|------------------|---------------------|
| SQG3/AV/W | 666057FULL-0097X | SQG3 Base AV, White |